

## Expansion joint profile surface EJOT® Pro DFP-F

**DFP-F06/01: 8808048001**

### Application

Profile with glass fibre fabric for forming vertical building expansion joints in flat surface areas with thermal insulation composite systems.

### Properties

Precise and clean plaster connection; can be used for joint widths of 20 - 30 mm; good plaster adhesion due to grooved surface

### Storage and transport

lying on the entire surface; dry and frost-free; not above 50 °C; no direct sunlight

#### Dimensions and packaging

Bar length [m]	2.5
Pieces / cardboard box	25
Running meter / cardboard box	62.5
Cardboard box / pallet	33
Running meter / pallet	2,063
Pallet height [m]	1.3

#### Basic profile

Raw material	Rigid and soft PVC – free from lead and cadmium – REACH compliant
Tolerances	Profile general tolerances 2A according to DIN 16941
Colour fastness	According to DIN EN 20105-A03 – compliance level 2

#### Mesh

Glass fiber fabric	R131 or comparable (certified on the basis of EAD 040016-01-0404 / EAD 040083-00-0404)
Fabric grammage [g/m <sup>2</sup> ]	160
Mesh size [mm]	4 x 4
Fabric colour/print	White neutral
Fabric width [cm]	12.5 ± 5 %
Fabric fastening	welded

