

XT centring grommets F (fixed point)



Cross references

JT4-LT-XT-3H/4-5.5xL
 JT4-LT-XT-3H/6-5.5xL
 Cordless screwdriver
 ASCM QSW
 LT-XT Tool TX25

Application range

- > For fastening facade claddings in combination with LT-XT screws with head diameter 16 mm
- > To form fixed points

Properties

- > Grey coloured plastic
- > UV-resistant

Advantages

- > All holes in the facade cladding are produced with the same diameter (11 mm), which can be done efficiently at the shop floor
- > No rivet installation gauge, no drilling gauge necessary
- > Fast assembly in combination with LT-XT screws
- > Easily revisionable panel fastening
- > The 0.5 collar of the grommet prevents direct contact between screw head and panel surface
- > The hole in the middle serves for the centred positioning of the screw

Notice

Usability of grommets and LT-XT screws must be agreed with the respective panel manufacturer. Please note the respective approval for the exterior wall cladding and the assembly instructions of the manufacturer.

Applications



Product online



Order description	Internal hole diameter [mm]	Pre-drilling diameter [mm]	max. panel thickness [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
EJOT XT centring grommet Ø 11/4 F	5.8	11.0	4.0	500		3010013700	4061245044552