

Self-drilling screw JT4-LT-XT-3H/4-5.5x19



Cross references

Centring grommet F
Centring grommet S
Cordless screwdriver
ASCM QSW
LT-XT Tool TX25

Application range

- > For fastening facade cladding 2.0 mm to aluminium substructures ≤ 2.0 mm
- > Can be combined with LT fixed and sliding point grommets

Properties

- > A2 stainless steel
- > Pan head

Advantages

- > Also available as painted version
- > Flat screw head for aesthetic facade design
- > Wobble-free fastening by using the LT Tool
- > Easy assembly and reliable sliding thanks to optimised free spin zone
- > Centering grommet collar protects the facade cladding surface from scratches
- > No rivet installation gauge or drilling gauge necessary
- > XT cutting ring under the screw head facilitates easy removal of the protective film during the forming of fixed points without centring grommet. Advantage when using the fixed point grommet: all holes in the panel can be pre-drilled with $\varnothing 11$ mm
- > Non-threaded part under the screw head allows an intentional further rotation of the screw head after connecting surface


Notice

Please note the respective approval for the exterior wall cladding and the assembly instructions of the manufacturer.

Applications



Technical specifications



Certifications



Installation process



Product online



Order description	Length [mm]	max. panel thickness [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
JT4-LT-XT-3H/4-5.5x19 KD16	19	2.0	500		7384219300	4061245044507